

It is important to maximise the production possibilities that new automation provides. IST UV solutions are designed with optimum reliability as a priority and this is achieved by incorporating outstanding heat management possibilities and total production flexibility.

# THE UV PACKAGE FOR CRABTREE MARQUESS PLUS

## **URS® INLAY REFLECTOR TECHNOLOGY**


URS® reflectors are what are known as cold mirror reflectors, fitted with more than 60 different metal oxide layers that only reflect the UV light and deflect the thermal radiation to a water-cooled profile. These highly resistant reflectors boast an extremely long service life and optimum heat management.

The reflector inlays are force-fitted to the unit, facilitating an easy replacement of the half shells. For example, simple replacement of the reflectors is interesting if the curing result can be improved by a different reflector geometry or coating for specific printing jobs.

## **FLC® QUICK-CHANGE LAMPS**

The cordless FLC® UV lamp system enables lamps to be changed quickly and easily. It is possible to remove the UV lamp from the lamp unit with just one hand movement and a lamp replacement just takes a few seconds, thus saving users several hours of machine availability per year.





# F806 11/23 EN Subject to technical modifications IST and products / services marked with ® are registered trademarks of the METZ Group

# **COOLING SYSTEM**

Water-cooling of the shutters and reflectors ensures that excess heat is efficiently carried out of the press. Also, the integrated air-cooling provides for optimized output of the UV lamp as well as removing small traces of ozone.

## **ELECTRONIC POWER SUPPLY DEVICES**

Linked to the printing speed, the ELC® controller can continuously adjust the lamp output between around 30 and 100%. In standby mode, the power is automatically reduced to a minimum.

#### FLEXIBLE INTERCHANGE OF UV INTERDECK UNITS

When required, the UV interdeck units can be moved to different positions. A mechanical preparation of the respective printing station ensures easy movability.

## **OPERATOR FRIENDLY CONTROL SYSTEM UCS**

Complete operation of the UV unit is managed by the UCS control terminal, which is installed adjacent to the control desk of the press.


## **UV INTERDECK CURING**

- UV-unit placed on support brackets over sheettransport system
- Unit can easily be accessed for cleaning, lamp changing, etc.
- Plug-in power connections on the drive side

# **ALSO IN OUR PROGRAMME**

- UV Set-Stack units
- UV Undercure units
- UV Pre-Coater





Electrical lamp control (ELC®) for highest demands and best energy savings in UV printing

# > WE HAVE THE CURE