



ELC® X SERIES
MAINTENANCE-FREE WITH
MINIMUM SPACE REQUIREMENTS

The electronic power supply devices of the ELC® X series have been specially developed for operating UV lamps and LED modules where space is at a premium. They optimise production safety in the print room and also reduce operating costs. They contain all the components for process control.

THE POWERFUL ELECTRONIC SYSTEM OFFERS SEVERAL BENEFITS:

LOW OPERATING COSTS

The highly efficient ELC® X operates with low energy consumption. The UV unit can be operated in stand-by mode with output of 30%. Further savings can also be made depending on the local energy supply (eg. compensation plant, energy distribution and tariff classification).

INCREASED PRODUCTION SAFETY

Highly consistent output and accurate temperature control are ensured through the integrated output control of the ELC® X. Network voltage variations of $\pm 10\%$ do not affect the output due to the integrated control and monitoring system. Printing on sensitive materials can begin at a low output and accurate temperature control guarantees no distortion of heat-sensitive substrates even at reduced print speeds.

OUTPUT CONTROL

Total control of the output has two advantages. Firstly, lamp and LED can be switched to energy-saving stand-by mode (minimal setting) during long pauses. Secondly the output can be steplessly adjusted between 20 and 100% depending on the print speed.

HOT SWAP TECHNOLOGY

Hot Swap Technology enables the operation of UV and LUV systems. It is therefore possible to switch to the respective sister technology at any time.

OUTPUT

The ELC® X range includes power supply units suitable for almost all applications. ELC® X units are available for outputs up to 36 kW.

PERFORMANCE OF THE ELC® X ELECTRONIC POWER SUPPLY UNITS

- HotSwap and up to 97% electrical efficiency
- The ELC® X has a network power factor > 0.97. It can be operated directly from the network without any additional levies.
- Power factor correction (PFC) ensures that the harmonic content of the mains current is < 5%.
- UV lamps and LED have infinitely adjustable dimming over 20–100% of the nominal electrical output.
- Stacking concept
- Air cooled
- Configuration, control and monitoring are achieved by means of a Profibus interface, and the ELC® X units can be integrated in the system control without problem.
- The output is automatically adjusted to compensate for any variations in the network voltage.
- Safe in case of short circuits or idle running
- UV lamps: Integrated electronic lamp ignition
- Integrated electronic control and monitoring systems
- Integrated earth leakage detection
- Fully insulated output of UV lamps and LED modules



ELC®-X stacking concept

Technical data

Supply voltage:	400–480 V ±10 %
Output:	6–36 kW depending on unit type
Dimming range:	approx. 20–100 %
Power factor:	around 0.97 rating
Degree of protection:	IP 54
Dimensions:	ELC-X6: 125 x 470 x 320 mm (H x W x D) ELC-X8: 125 x 470 x 420 mm (H x W x D) ELC-X12: 125 x 470 x 420 mm (H x W x D) ELC-X16: 250 x 470 x 420 mm (H x W x D) ELC-X24: 250 x 470 x 420 mm (H x W x D) ELC-X36: 375 x 470 x 420 mm (H x W x D)
Weight:	14–41 kg depending on unit type

WE HAVE THE CURE

IST METZ GmbH & Co. KG
Lauterstraße 14–18 | 72622 Nürtingen | Germany
Tel.: +49 7022 6002-0 | Fax: +49 7022 6002-76
E-Mail: info@ist-uv.com

IST France Sarl | info@fr.ist-uv.com
IST (UK) Limited | info@uk.ist-uv.com
IST America – U.S. Operations, Inc. | info@usa.ist-uv.com
IST Italia S.r.l. | info@it.ist-uv.com
IST Benelux B.V. | info@bnl.ist-uv.com

IST METZ UV Equipment China Ltd. Co. | info@cn.ist-uv.com
UV-IST Ibérica SLU | info@es.ist-uv.com
IST Nordic AB | info@se.ist-uv.com
IST METZ SEA Co., Ltd. | info@th.ist-uv.com